


**Instrument Data Sheet**

General	1	Product	Flow Detection Control (Dual Rated)
	2	Model Number	FS-4D
	3	Manufacturer	Conveyor Components Company
	4		
Environment	5	Ambient Temperature	-50 to +40 °C (-58 to +104 °F)
	6	Enclosure Material	319 cast aluminum
	7	Enclosure Rating	NEMA Type 3S, 4, 4X, 5; Type 9: Class II (Div. 1 & 2), Groups E, F & G
	8	Mounting	3 holes at $\varnothing^{13/32}$ " (Surface mount)
	9		
	10		
Switch	11	Switch Type	DPDT x 1
	12	Contact Type	Dry contact
	13	Contact Rating	15A @ 125V or 250V AC; ¼ hp 125V AC; 1 ½ hp 250V AC
	14	Electrical Action	Non-latching
	15	Electrical Connection	¾" NPT x 1
	16	Indicating Lamp	None
	17		
	18		
	19		
Actuator	20	Type	Flow detector
	21	Mechanism	Counterweighted paddle with rotating cam
	22	Non-activated Position	Field adjustable neutral position 0° to 360°
	23	Activated Position	Field adjustable: 0° to 45° from neutral (shaft rotation is not bound by the activation limit)
	24	Range of Travel	Practical range is application and user defined; infinite bi-directional shaft rotation is possible
	25	Action	Non-latching
	26	Actuation Force	Field adjustable counterweight
	27		
	28		
	29		
Options	30	Finish	Uncoated (standard) or epoxy (option E) coating available
	31		
	32		
	33		
	34		
	35		
	36		
Certifications	37	UL Certification File	NMFT.E83971, NOIV.E71075
	38	cUL Certification File	NMFT7.E83971, NOIV7.E71075
	39		
Manufacturer	40		Conveyor Components Company Division of Material Control, Inc. 130 Seltzer Road, PO Box 167 Croswell, MI 48422 USA (810) 679-4211 info@conveyorcomponents.com www.conveyorcomponents.com
Notes:			