


Instrument Data Sheet

General	1	Product	Vertical Belt Alignment Control (Explosion Proof)
	2	Model Number	VA-X
	3	Manufacturer	Conveyor Components Company
	4		
Environment	5	Operating Temperature	-10 to 82 °C [14 to 179 °F]
	6	Chassis Material	Powder coated steel
	7	Microswitch Enclosure Material	Powder coated aluminum
	8	Microswitch Enclosure Rating	NEMA Type 1, 3, 4, 6, 13; Type 7: Class I (Div. 1 & 2), Groups B, C & D; Type 9: Class II (Div. 1 & 2), Groups E, F & G
	9	Mounting	Six holes at $\varnothing^{13/32}$ [10 mm]; mounted through chute wall
	10		
Electrical	11	Switch Type	Sequential double break (different activating position for each pole)
	12	Contact Type	Dry contact
	13	Contact Rating	Max 10A (thermal); max 600V AC; Max 250V DC
	14	Electrical Action	Non-latching
	15	Electrical Connection	$\frac{3}{4}$ " NPT x 1
	16	Indicating Lamp	None
	17		
	18		
	19		
Actuator	20	Type	Belt alignment control for vertical belts
	21	Mechanism	Roller on sprung lever
	22	Inactivated State	Field-adjustable roller pitch: 25° to 90° from vertical
	23	Pole 1 Activation State	15° from resting position
	24	Pole 2 Activation State	25° from resting position
	25	Action	Non-latching
	26		
	27		
	28		
Options	29		
	30		
	31		
	32		
	33		
	34		
	35		
Certifications	36		
	37	UL Certification File	Microswitch : E61730
	38	CSA Certification File	Microswitch : LR57327
	39		
Manufacturer	40		Conveyor Components Company Division of Material Control, Inc 130 Seltzer Road, PO Box 167 Crosswell, MI 48422 USA (810) 679-4211 info@conveyorcomponents.com www.conveyorcomponents.com
Notes: 1. Typically used in pairs to provide proper protection.			