


Instrument Data Sheet

General	1	Product	Tripper Position Control
	2	Model Number	TA-1-TPS
	3	Manufacturer	Conveyor Components Company
	4		
Environment	5	Certified Ambient Temperature Rating	40 °C [104 °F]
	6	Functional Ambient Temperature	-50 to 40 °C [-58 to 104 °F]
	7	Enclosure Material	319 cast aluminum
	8	Enclosure Rating	NEMA Type 3S, 4, 4X, 5
	9	Mounting	3 holes at $\varnothing^{13/32}$ " (Surface mount)
	10		
Switch	11	Switch Type	SPDT x 1
	12	Contact Type	Dry contact
	13	Contact Rating	20A @ 125V, 250V or 480V AC; 10A @ 125V AC inductive; 1 hp 125V AC; 2 hp 250V AC, ½ A @ 125 V DC; ¼ A @250 V DC
	14	Electrical Action	Non-latching
	15	Electrical Connection	¾" NPT x 1
	16	Indicating Lamp	None
	17		
	18		
	19		
Actuator	20	Type	Tripper Position Control
	21	Mechanism	Acetal roller on a sprung lever with rotating cam
	22	Non-activated Position	Field adjustable neutral position 0° to 360°
	23	Activated Position	Field adjustable: 0° to 45° from neutral (roller travel is not bound by the activation limit)
	24	Range of Travel	Bi-directional 0° to 90° from neutral
	25	Action	Non-latching
	26		
	27		
	28		
	29		
Options	30	Finish	Uncoated (standard) or epoxy coating (option E)
	31		
	32		
	33		
	34		
	35		
	36		
Certifications	37	UL Certification File	NMFT.E83971
	38	cUL Certification File	NMFT7.E83971
	39		
Manufacturer	40		Conveyor Components Company Division of Material Control, Inc. 130 Seltzer Road, PO Box 167 Croswell, MI 48422 USA (810) 679-4211 info@conveyorcomponents.com www.conveyorcomponents.com
Notes:			